



IWATSU
ICON[™]
series

ICON (i'kon) n. **1.** An image; a representation. **2.** An important and enduring symbol. **3.** An object of great attention and respect.

Iwatsu ICON Series

When the design process for the Iwatsu ICON Series was first set into motion, the goal was to design a business phone that would push the technological envelope without becoming overly complicated. To achieve this, hundreds of hours of research was compiled in design sessions, focus groups and surveys with laymen and industry experts alike.

Armed with this data, our design and engineering teams set out to create a business extension specifically for small to medium-sized businesses. The goal: create a phone rugged enough for industrial applications, intuitive enough for courtesy use and with enough advanced features for even the most ardent power user. We also demanded that all this fit into a station that looks as attractive as it sounds. Our higher standards produced the Iwatsu ICON Series.

Iwatsu ICON IX-5930 IP Phone



- ▶ 15-line, 24-character LCD with backlight
- ▶ Oversized incoming call / message waiting indicator lamp
- ▶ 30 self-labeling flexible feature keys with red and green LEDs (Times 2 screens)
- ▶ Ergonomic handset design
- ▶ Full-duplex speakerphone
- ▶ Optional integrated Bluetooth® headset interface
- ▶ Power Over Ethernet or local power supply
- ▶ Integrated wall mount

Iwatsu ICON IX-5800 Digital Phone



- ▶ 2-line, 16-character LCD
- ▶ Oversized incoming call / message waiting indicator lamp
- ▶ 9 programmable flexible feature keys with red and green LEDs, expandable to 18
- ▶ 5 fixed feature keys
- ▶ Headset jack
- ▶ Full-duplex speakerphone
- ▶ Integrated wall mount

Iwatsu ICON IX-5910 IP & IX-5810 Digital Phone



- ▶ 7-line, 24-character LCD with backlight
- ▶ Oversized incoming call / message waiting indicator lamp
- ▶ 10 self-labeling flexible feature keys with red and green LEDs (Times 2 screens)
- ▶ 16 programmable feature keys with red and green LEDs, expandable to 24
- ▶ Full-duplex speakerphone
- ▶ Optional integrated Bluetooth® headset interface
- ▶ VoIP version operates with Power Over Ethernet or local power supply
- ▶ Integrated wall mount

Bluetooth® Headset Interface – Enjoy the convenience and mobility of using a single Bluetooth® headset for both your cell phone and desk phone. The optional Bluetooth® headset interface for the ICON series IX-5810, IX-5910 and IX-5930 phones allows users to pair a Bluetooth® headset with their phone.

Interactive Information Display – Iwatsu Text Web allows users to interactively access and display data retrieved from the Internet, intranet or corporate databases on your phone – including select RSS feeds.

Full Duplex Speakerphone – All Iwatsu ICON Series phones are equipped with a full-duplex speakerphone for superior voice clarity during hands-free calls.

Electronic Bulletin Board – Be Informed! – Iwatsu Ticker Display allows companies to provide important messages to their employees such as security alerts, local weather or other customizable company announcements by scrolling information across the station display.

Easy Feature Operation – Features such as conference calling, directory speed dialing and call forwarding are a breeze with the Iwatsu ICON Series phones.

Self-Labeling Feature Keys – Make it YOURS! Customize your telephone with access to features you need. The Iwatsu ICON Series IX-5810, IX-5910 and IX-5930 phones support user-programmable feature key assignments that display the exact button function on the LCD.

BUSINESS EXTENSIONS.

Phone	IX-5800	IX-5810	IX-5910	IX-5930
3-Position Integrated Pedestal	Standard	Standard	Standard	Standard
Voice Switching	TDM	TDM	IP	IP
Self-Labeling Keys	Not Applicable	10 Keys by 2 Screens; 20 Feature Keys Max	10 Keys by 2 Screens; 20 Feature Keys Max	30 Keys by 2 Screens; 60 Feature Keys Max
Multipurpose Keys	9 Keys	16 Keys	16 Keys	Not Applicable
Optional Line Key Expansion Unit	9 Additional Keys	8 Additional Keys	8 Additional Keys	Not Applicable
Bluetooth Headset Interface	Not Applicable	Optional	Optional	Optional
Display	2-Line, 16-Character	7-Line, 24-Character	7-Line, 24-Character	15-Line, 24-Character
Programmable Backlight	Unavailable	Standard	Standard	Standard
Voice Compression	Not Applicable	Not Applicable	G.711 or G.729	G.711 or G.729
QoS	Not Applicable	Not Applicable	IEEE802.1p or TOS/DSCP	IEEE802.1p or TOS/DSCP
Maximum Distance	Up to 2,100 Feet	Up to 2,100 Feet	Ethernet Maximum	Ethernet Maximum
Power Supply	Line-Powered	Line-Powered	POE or Local Power Connection	POE or Local Power Connection

